

TYPE APPROVAL CERTIFICATE**This is to certify:****That the Electric Power Cable**with type designation(s)
RU P18 0,6/1 kV

Issued to

Nuhas Oman LLC
Sultanate of Oman, Oman

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****General power and lighting.****Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.****Rated voltage (kV) 0,6/1**
Temp. class (°C) 90Issued at **Høvik** on **2019-09-10**for **DNV GL**This Certificate is valid until **2023-12-31**.DNV GL local station: **New Building Dubai**Approval Engineer: **Ivar Bull****Trond Sjøvåg**
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Type: RU P18 0,6/1 kV

Construction:

Conductors: Tinned, stranded copper class 2 or class 5
 Core insulation: EPR or HFEPR
 Outer sheath: SHF2 or SHF Mud

| No of cores: | Cross sectional area [mm ²] |
|-------------------|---|
| 1 | 10 - 630 |
| 2 | 1,5 - 120 |
| 3, 4 | 1,5 - 300 |
| 5 | 1,5 - 120 |
| 7, 12, 19, 27, 37 | 1,5 - 2,5 |

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Data sheet : Doc no.: NO/TEC/TP/RU/DNV/1kV Date: 03/09/2013

Test report : dated 25/6-2014

Tests carried out

| | Release | General description | Limitation |
|----------------|---------|--|---|
| DNVGL-CP-0399 | 2016-03 | Class Programme Electric cables | |
| IEC 60092-350 | 2014-08 | General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications | |
| IEC 60092-360 | 2014-04 | Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables. | |
| IEC 60092-353 | 2016-09 | Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV | |
| IEC 60332-3-22 | 2009-02 | Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A | Bunch test Category A |
| IEC 60754-1 | 2011-11 | Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content | Low Halogen: <0,5% Halogen |
| IEC 60754-2 | 2011-11 | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity | Halogen free: pH > 4,3 Conductivity < 10µS/mm |

Job Id: **262.1-032020-1**
Certificate No: **TAE00003N8**

| | Release | General description | Limitation |
|---------------|--------------------|---|--|
| IEC 61034-1/2 | 2013-07 2013-09 | Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements | Low smoke Light transmittance $\geq 60\%$ |
| NEK TS606 Ed5 | 2016 | Cables for offshore installations - halogen-free low smoke flame-retardant / fire-resistant (HFFR-LS). Technical specification. | Mud resistance test: Required Max variations \pm : IRM902 & 903 100°C 7d. TS & E@B, weight & vol.: $\pm 30\%$ Calc. Bromide 70°C 56d. TS & E@B: $\pm 25\%$, weight: $\pm 15\%$, vol.: $\pm 20\%$ Oil based mud: EDC 95/11 70°C 56d TS & E@B $\pm 30\%$, weight & vol.: $\pm 25\%$ |

Marking of product

Nuhas Oman LLC – RU P18 – size – 0,6/1 kV – IEC 60332-3-22 – Lot No

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE